



# R-17-A-73 Asphalt Coating/Primer

## **SELECTION & SPECIFICATION DATA**

Type Oxidized Asphalt Cutback

**Description** R-17-A-73 Asphalt Coating/Primer is a metal corrosion

protection coating and asphalt primer packaged in a convenient aerosol spray can. It offers just the right amount

of product for small jobs and touch up work.

• Packaged in convenient aerosol spray can

ANSI/NSF 61 certified

· Penetrating and sealing primer

· Quick drying (less than 5 minutes dry-to-touch)

• Metal corrosion protection

Potable water service

· Paving maintenance

Roofing primer

• Ductile iron pipe and fittings (ID & OD)

Vehicle underbody

Color Black

Finish Gloss

**Topcoats** Asphalt, acrylics, epoxies, polyurethanes.

 $Consult \, Ergon Armor \, for \, more \, information.$ 

Dry Film

Thickness (DFT)

1 - 2 mils per coat

### **SUBSTRATES & SURFACE PREPARATION**

All surfaces must be clean and free from debris

and loose scale material or anything that may interfere with adhesion or act as a bond breaker

with the desired substrate.

**Cleanup** Mineral spirits or equivalent solvent.

#### **PACKAGING, ESTIMATING & HANDLING**

ITEM# PACKAGING

K-5136-7QD-001 Aerosol Can - 15 ounces

Theoretical Coverage

Rate

40 square feet per can at 2 coats

Storage & Shelf Life

Estimated shelf life is 24 months when stored in a dry area at 75°F (24°C). Actual shelf life may vary with storage conditions. Do not store below 40°F (4°C) or above 110°F (43°C). Store indoors. Always inspect the product prior to

use.

**SAFETY** 

**Safety** Mixes and applications of this product present a number of

hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using.

**Ventilation** Thorough air circulation must be used during and after

application until the product is cured. User should test and monitor exposure levels to ensure all personnel are within safe limits. Consult product SDS for further information.

Rev. 05/2025

#### **TERMS AND CONDITIONS OF SALE**

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see ergonarmor.com.