

1. Identification

| | |
|---|---|
| Product identifier | R-17-A-73 ASPHALT COATING/PRIMER |
| Other means of identification | None. |
| Recommended use | NSF/ANSI 61 Certified Asphalt Coating & Primer |
| Recommended restrictions | None known. |
| Manufacturer/Importer/Supplier/Distributor information | |
| Company Name | ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc. |
| Address | 2829 Lakeland Drive Jackson, MS 39232 USA |
| After hours telephone number | 1-800-222-7122 |
| Normal work hours telephone number | 1-877-982-7667 |
| Website | www.ergonarmor.com |
| E-mail | sds@ergon.com |
| Emergency 24-hour telephone number | CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887 |
| Information on operation hours | 8:00 a.m. to 5:00 p.m. |

2. Hazard(s) identification

| | | |
|------------------------------|---|-----------------------------|
| Physical hazards | Flammable aerosols | Category 1 |
| | Gases under pressure | Liquefied gas |
| Health hazards | Skin corrosion/irritation | Category 2 |
| | Germ cell mutagenicity | Category 1B |
| | Carcinogenicity | Category 1B |
| | Specific target organ toxicity, single exposure | Category 3 narcotic effects |
| | Aspiration hazard | Category 1 |
| Environmental hazards | Not classified. | |
| OSHA defined hazards | Not classified. | |

Label elements


| | |
|--------------------------------|--|
| Signal word | Danger |
| Hazard statement | Contains gas under pressure; may explode if heated. May cause cancer. May be fatal if swallowed and enters airways. Extremely flammable aerosol. Causes skin irritation. May cause drowsiness or dizziness. May cause genetic defects. |
| Precautionary statement | |
| Prevention | Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Pressurized container: Do not pierce or burn, even after use. Wear protective gloves/protective clothing/eye protection/face protection. Do not spray on an open flame or other ignition source. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. |
| Response | IF ON SKIN: Wash with plenty of soap and water. Specific treatment see Section 4 of this SDS. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF exposed or concerned: Get medical advice/attention. |

| | |
|--|--|
| Storage | Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Hazard(s) not otherwise classified (HNOC) | None known. |
| Supplemental information | Not applicable. |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|----------------|--------------------------|------------|---------|
| ASPHALT | | 64742-93-4 | 30 - 50 |
| VM&P NAPHTHA | | 64742-89-8 | 25 - 45 |
| DIMETHYL ETHER | | 115-10-6 | 0 - 40 |

4. First-aid measures

| | |
|---|--|
| Inhalation | Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. For breathing difficulties, oxygen may be necessary. Get medical attention, if needed. Call a physician if symptoms develop or persist. |
| Skin contact | Take off immediately all contaminated clothing. Wash off immediately with plenty of water. Wash off with soap and water. Rinse skin with water/shower. Get medical attention if irritation develops and persists. For minor skin contact, avoid spreading material on unaffected skin. Take off contaminated clothing and wash before reuse. |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. Rinse with water. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately. Get medical attention if irritation develops and persists. |
| Ingestion | Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention if symptoms occur. If ingestion of a large amount does occur, call a poison control center immediately. |
| Most important symptoms/effects, acute and delayed | Direct contact with eyes may cause temporary irritation. |
| Indication of immediate medical attention and special treatment needed | Treat symptomatically. |
| General information | In case of shortness of breath, give oxygen. Get medical attention if symptoms occur. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. |

5. Fire-fighting measures

| | |
|--|---|
| Suitable extinguishing media | Foam. Dry powder. Carbon dioxide (CO2). |
| Unsuitable extinguishing media | Water. Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | During fire, gases hazardous to health may be formed. Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Oxides of nitrogen and sulfur may also be formed. |
| Special protective equipment and precautions for firefighters | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. |
| Fire fighting equipment/instructions | Stop leak if you can do so without risk. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unnecessary personnel away. Ensure adequate ventilation. Wear appropriate personal protective equipment. Keep people away from and upwind of spill/leak.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Prevent entry into waterways, sewer, basements or confined areas.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid prolonged exposure. Observe good industrial hygiene practices. Keep away from sources of ignition - No smoking. Avoid contact with skin. Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray.

Conditions for safe storage, including any incompatibilities

Store in a closed container away from incompatible materials. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Refrigeration recommended. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value |
|-------------------------------|------|----------------------------------|
| VM&P NAPHTHA (CAS 64742-89-8) | PEL | 400 mg/m ³ 100 ppm |

U.S. - NIOSH Components

| Components | Type | Value |
|--------------------------|------|---------------------|
| ASPHALT (CAS 64742-93-4) | REL | 5 mg/m ³ |

US. NIOSH: Pocket Guide to Chemical Hazards Components

| Components | Type | Value |
|-------------------------------|------|----------------------------------|
| VM&P NAPHTHA (CAS 64742-89-8) | TWA | 400 mg/m ³ 100 ppm |

US. Workplace Environmental Exposure Level (WEEL) Guides Components

| Components | Type | Value |
|-------------------------------|------|------------------------------------|
| DIMETHYL ETHER (CAS 115-10-6) | TWA | 1880 mg/m ³ 1000 ppm |

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear protective gloves.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

Physical state Liquid.

Form Liquid.

Color Not available.

Odor Not available.

Odor threshold Not available.

pH Not available.

Melting point/freezing point -222.7 °F (-141.5 °C) estimated

Initial boiling point and boiling range -12.68 °F (-24.82 °C) estimated

Flash point -42.0 °F (-41.1 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 3.4 % estimated

Explosive limit - upper (%) 27 % estimated

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 550 °F (287.78 °C) estimated

Decomposition temperature Not available.

Viscosity Not available.

Other information

Specific gravity 0.3229 estimated

VOC < 500 g/l

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Avoid temperatures exceeding the flash point. Heat, flames and sparks. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products Carbon monoxide. Volatile hydrocarbon vapors.

11. Toxicological information**Information on likely routes of exposure**

Inhalation Prolonged inhalation may be harmful. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Skin contact Causes skin irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Breathing of high vapor concentrations may cause dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

| Product | Species | Test Results |
|----------------------------------|---------|-------------------|
| R-17-A-73 ASPHALT COATING/PRIMER | | |
| Acute Inhalation | | |
| LC50 | Rat | 175 mg/l, 4 Hours |

| Components | Species | Test Results |
|-------------------------------|---------|---------------------|
| DIMETHYL ETHER (CAS 115-10-6) | | |
| Acute Inhalation | | |
| LC50 | - | 164000 ppm, 4 Hours |

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 64742-93-4) 2A Probably carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

| Product | Species | Test Results |
|----------------------------------|---------|-----------------------------|
| R-17-A-73 ASPHALT COATING/PRIMER | | |
| Aquatic | | |
| Crustacea | EC50 | Daphnia |
| | | 12.5, 48 hours |
| Fish | LC50 | Fish |
| | | 30, 96 hours |
| <i>Acute</i> | | |
| Crustacea | EC50 | Daphnia |
| | | 9, 48 hours estimated |
| Fish | LC50 | Fish |
| | | 29.3333, 96 hours estimated |

| Components | Species | Test Results |
|-------------------------------|---------|---|
| VM&P NAPHTHA (CAS 64742-89-8) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia pulex) |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) |
| | | >= 2.7 - <= 5.1 mg/l, 48 hours |
| | | 8.8, 96 hours |
| | | 8.8, 96 hours |
| <i>Acute</i> | | |
| Crustacea | EC50 | Water flea (Daphnia pulex) |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) |
| | | >= 2.7 - <= 5.1 mg/l, 48 hours |
| | | 8.8, 96 hours |
| | | 8.8, 96 hours |

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

DIMETHYL ETHER 0.1

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1

Subsidiary risk -

Label(s) 2.1

Packing group Not available.

Special precautions for user Not available.

Special provisions N82

Packaging exceptions 306

Packaging non bulk None

Packaging bulk None

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1

Subsidiary risk -

Packing group Not available.

Environmental hazards No.

ERG Code 10L

Special precautions for user Not available.
Other information
Passenger and cargo aircraft Allowed with restrictions.
Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950
UN proper shipping name Aerosols, flammable
Transport hazard class(es)
Class 2.1
Subsidiary risk -
Packing group Not available.
Environmental hazards
Marine pollutant No.
EmS F-D, S-U
Special precautions for user Not available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

DIMETHYL ETHER (CAS 115-10-6) Listed.
VM&P NAPHTHA (CAS 64742-89-8) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
Gas under pressure
Skin corrosion or irritation
Germ cell mutagenicity
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

DIMETHYL ETHER (CAS 115-10-6)

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

VM&P NAPHTHA (CAS 64742-89-8)

California Proposition 65



WARNING: WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT (CAS 64742-93-4)

Listed: January 1, 1990

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Industrial Chemicals (AICIS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | Yes |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| Taiwan | Taiwan Chemical Substance Inventory (TCSI) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 04-25-2022
Version # 01
NFPA ratings Health: 2
Flammability: 4
Instability: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

Product and Company Identification: Alternate Trade Names
Hazard(s) identification: Response
Hazard(s) identification: Prevention
Hazard(s) identification: Hazard statement
Composition / Information on Ingredients: Ingredients
Physical & Chemical Properties: Multiple Properties
HazReg Data: North America
GHS: Classification