SAFETY DATA SHEET



1. Identification

Product identifier NOVOCOAT™ EP3300 PASTE/CAULK PART B

Other means of identification None.

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

number

1-800-222-7122

Normal work hours

telephone number

1-877-982-7667

Website www.ergonarmor.com E-mail sds@ergon.com

Emergency 24-hour telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

hours

8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 1

> Serious eye damage/eye irritation Category 1 Sensitization, respiratory Category 1 Sensitization, skin Category 1 Germ cell mutagenicity Category 2 Specific target organ toxicity, repeated Category 2

exposure

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye

damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing genetic defects. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions

before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Wear protective aloves/protective clothing/eve protection/face protection. In case of inadequate ventilation wear

respiratory protection.

Material name: NOVOCOAT™ EP3300 PASTE/CAULK PART B

If skin irritation or rash occurs, seek medical attention. IF SWALLOWED: Rinse mouth. Do NOT Response

induce vomiting. If experiencing respiratory symptoms: Call a POISON CENTER or

doctor/physician. IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. Specific treatment (see this label). Take off contaminated clothing and wash before reuse. IF ON

SKIN: Wash with plenty of soap and water. IF exposed or concerned: Get medical

advice/attention.

Store locked up. Storage

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
BENZYL ALCOHOL		100-51-6	25 - 35
4,4'-METHYLENEBIS(CYCLOHEXYLA MINE)		1761-71-3	15 - 25
QUARTZ		14808-60-7	10 - 20
[3-(Aminomethyl)phenyl]methanam ne	ii	1477-55-0	5 - 15
[(DIMETHYLAMINO)METHYL]PHEN OL		25338-55-0	1 - 10
3-AMINOPROPYLTRIETHOXYSILANI	Ξ	919-30-2	< 1
BENZENE, HYDROXY-		108-95-2	< 1
DOLOMITE		16389-88-1	< 0.2
MAGNESIUM CARBONATE		546-93-0	< 0.2
CARBON BLACK	·	1333-86-4	0.02
Other components below reportable	e levels		30 - 40

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Wash Skin contact

contaminated clothing before reuse.

Eye contact Rinse with water. Continue to rinse for at least 15 minutes. Get medical attention if irritation

persists after washing.

Ingestion Rinse mouth. Do not induce vomiting. If vomiting occurs, the head should be kept low so that

stomach vomit doesn't enter the lungs. Call a POISON CENTER or doctor/physician if you feel

Most important

symptoms/effects, acute and

delaved

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special

treatment needed

Treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Material name: NOVOCOAT™ EP3300 PASTE/CAULK PART B

SDS US 5549 Version #: 03 Revision date: 10-21-2021 Issue date: 06-12-2020 2/9

and precautions for firefighters

Special protective equipment Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk, Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Value

Value

0.1 mg/m3

Form

Form

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

7. Handling and storage

Precautions for safe handling Avoid prolonged exposure. Observe good industrial hygiene practices.

Type

Type

Ceiling

Conditions for safe storage,

Store in original tightly closed container.

including any incompatibilities

Components

8. Exposure controls/personal protection

Occupational exposure limits

Components	. , pc	value	
BENZENE, HYDROXY- (CAS 108-95-2)	PEL	19 mg/m3	
		5 ppm	
Carbon Black (Cas 1333-86-4)	PEL	3.5 mg/m3	
MAGNESIUM CARBONATE (CAS 546-93-0)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 (29 CFR 19:	10.1000)		
Components	Туре	Value	Form
DOLOMITE (CAS 16389-88-1)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.

Material name: NOVOCOAT™ EP3300 PASTE/CAULK PART B

US. ACGIH Threshold Limit Values

[3-(Aminomethyl)phenyl]me

thanamine (CAS 1477-55-0)

Components

SDS US 5549 Version #: 03 Revision date: 10-21-2021 Issue date: 06-12-2020

US. ACGIH Threshold Limit Value Components	es Type	Value	Form
BENZENE, HYDROXY- (CAS 108-95-2)	TWA	5 ppm	
CARBON BLACK (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	Form
[3-(Aminomethyl)phenyl]me thanamine (CAS 1477-55-0)	Ceiling	0.1 mg/m3	
BENZENE, HYDROXY- (CAS 108-95-2)	Ceiling	60 mg/m3	
		15.6 ppm	
	TWA	19 mg/m3	
		5 ppm	
CARBON BLACK (CAS 1333-86-4)	TWA	0.1 mg/m3	
MAGNESIUM CARBONATE (CAS 546-93-0)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
US. Workplace Environmental Ex	posure Level (WEEL) Guides		
Components	Туре	Value	
BENZYL ALCOHOL (CAS 100-51-6)	TWA	44.2 mg/m3	
		10 ppm	

Biological limit values

ACGIH Biological	Exposure Indices
Components	Value

Components	Value	Determinant	Specimen	Sampling Time
BENZENE, HYDROXY- (CAS 108-95-2)	250 mg/g	Phenol with hydrolysis	Creatinine in urine	*

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

Exposure guidelines

Appropriate engineering

US - California OELs: Skin designation

Can be absorbed through the skin. [3-(Aminomethyl)phenyl]methanamine (CAS 1477-55-0) BENZENE, HYDROXY- (CAS 108-95-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

BENZENE, HYDROXY- (CAS 108-95-2) Skin designation applies.

US - Tennessee OELs: Skin designation

Can be absorbed through the skin. [3-(Aminomethyl)phenyl]methanamine (CAS 1477-55-0) BENZENE, HYDROXY- (CAS 108-95-2) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

[3-(Aminomethyl)phenyl]methanamine (CAS 1477-55-0) Can be absorbed through the skin. BENZENE, HYDROXY- (CAS 108-95-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

[3-(Aminomethyl)phenyl]methanamine (CAS 1477-55-0) Can be absorbed through the skin. BENZENE, HYDROXY- (CAS 108-95-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

BENZENE, HYDROXY- (CAS 108-95-2) Can be absorbed through the skin.

controls occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Wear safety glasses; chemical goggles (if splashing is possible) Eye/face protection

^{* -} For sampling details, please see the source document.

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear qauntlet style

gloves.

Other Wear suitable protective clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

9. Physical and chemical properties

Paste. **Appearance Physical state** Liquid. **Form** Paste. Color Various.

Odor Ammoniacal. Amine-like.

Odor threshold Not available. рH Alkaline Melting point/freezing point Not available. Initial boiling point and Not available.

boiling range

Not available. Flash point **Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit -

upper (%)

Not available.

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Not available. Vapor pressure Not available. Vapor density Not available. Relative density

Solubility(ies)

Solubility (water) **Partial**

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Not available. **Viscosity**

Other information

Density 11.72 lb/gal estimated

Specific gravity 1.40 estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause sensitization by inhalation.

Skin contact May cause an allergic skin reaction. Causes severe skin burns and eye damage

Eye contact Causes serious eye damage. Ingestion May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Causes serious eye damage. May cause an allergic skin reaction.

Information on toxicological effects

Acute toxicity

Components **Species Test Results** BENZYL ALCOHOL (CAS 100-51-6) Acute

Dermal

LD50 Rabbit 2000 mg/kg

Inhalation

LC50 Rat 1000 mg/l, 8 Hours

CARBON BLACK (CAS 1333-86-4)

Acute Oral

LD50 Rat > 8000 mg/kg

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

Causes eye burns.

irritation

Respiratory or skin sensitization

Respiratory sensitization May cause allergy or asthma symptoms or breathing difficulties if inhaled

Skin sensitization May cause sensitization by skin contact.

Germ cell mutagenicity Known or suspected mutagen.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. This product

contains crystalline silica. Silica is a known carcinogen; however in this encapsulated form the

normal routes of exposure are unavailable.

IARC Monographs. Overall Evaluation of Carcinogenicity

BENZENE, HYDROXY- (CAS 108-95-2) 3 Not classifiable as to carcinogenicity to humans.

CARBON BLACK (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7)

US. National Toxicology Program (NTP) Report on Carcinogens

QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Not classified.

Not available. **Aspiration hazard**

SDS US

^{*} Estimates for product may be based on additional component data not shown.

12. Ecological information

Ecotoxicity The product contains a substance which is toxic to aquatic organisms.

Product		Species	Test Results
NOVOCOAT™ EP3300	PASTE/CAULK PART	В	
Aquatic			
Crustacea	EC50	Daphnia	4444.7607 mg/l, 48 hours estimated
Fish	LC50	Fish	903.2863 mg/l, 96 hours estimated
Components		Species	Test Results
BENZENE, HYDROXY-	(CAS 108-95-2)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia obtusa)	4.7 - 6.4 mg/l, 48 hours
Fish	LC50	Asiatic knifefish (Notopterus notopterus)	8 - 8.25 mg/l, 96 hours
BENZYL ALCOHOL (CA	AS 100-51-6)		
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	10 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

BENZENE, HYDROXY-1.46 BENZYL ALCOHOL 1.1

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions When this product as supplied is to be discarded as waste, it does not meet the definition of a

RCRA waste under 40 CFR 261.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues /

Dispose of in accordance with local regulations. Empty containers or liners may retain some product unused products residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

UN number UN3082

UN proper shipping name ENVIRONMENATALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S (BENZENE, HYDROXY-)

Transport hazard class(es)

Class 9 **Subsidiary risk** Packing group III **Environmental hazards**

> Marine pollutant No.

Material name: NOVOCOAT™ EP3300 PASTE/CAULK PART B


SDS US

EmS Not available. Special precautions for Not available.

Transport in bulk according to Not available. Annex II of MARPOL 73/78

and the IBC Code

IMDG



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

BENZENE, HYDROXY- (CAS 108-95-2) Listed.

SARA 304 Emergency release notification

BENZENE, HYDROXY- (CAS 108-95-2) 1000 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7)

Cancer lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

SAILA SOL EXCICITELY	iazai aoas sabsta					
Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)	
BENZENE, HYDROXY-	108-95-2	1000		500	10000	

SARA 311/312

Yes

Hazardous chemical

Classified hazard Skin corrosion or irritation

categories

Serious eye damage or eye irritation Respiratory or skin sensitization

Germ cell mutagenicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
BENZENE, HYDROXY-	108-95-2	< 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

BENZENE, HYDROXY- (CAS 108-95-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Material name: NOVOCOAT™ EP3300 PASTE/CAULK PART B

5549 Version #: 03 Revision date: 10-21-2021 Issue date: 06-12-2020

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

BENZENE, HYDROXY- (CAS 108-95-2)

Low priority

US state regulations

California Proposition 65



WARNING: California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is

not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

CARBON BLACK (CAS 1333-86-4) Listed: February 21, 2003 QUARTZ (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

BENZENE, HYDROXY- (CAS 108-95-2) CARBON BLACK (CAS 1333-86-4) DOLOMITE (CAS 16389-88-1)

MAGNESIUM CARBONATE (CAS 546-93-0)

QUARTZ (CAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

 Issue date
 06-12-2020

 Revision date
 10-21-2021

 Varion #
 03

Version # 03

United States & Puerto Rico

NFPA ratings Health: 3

Flammability: 0 Instability: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Physical & Chemical Properties: Multiple Properties

Toxicological Information: Toxicological Data Transport information: General information

GHS: Classification

Material name: NOVOCOAT™ EP3300 PASTE/CAULK PART B

5549 Version #: 03 Revision date: 10-21-2021 Issue date: 06-12-2020 9 / 9

Yes