SAFETY DATA SHEET



1. Identification

Product identifier NOVOCOAT™ EP3300 PASTE/CAULK PART B

Other means of identification None.

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive

Jackson, MS 39232

1-800-222-7122

USA

After hours telephone

Aiter nours telephone

number

Normal work hours

telephone number

1-877-982-7667

Website www.ergonarmor.com

E-mail sds@ergon.com

Emergency 24-hour telephone number Information on operation hours

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 1

Serious eye damage/eye irritation

Category 1

Sensitization, respiratory

Category 1

Sensitization, skin

Category 1

Germ cell mutagenicity

Category 2

Specific target organ toxicity, repeated

Category 2

exposure

Environmental hazardsNot classified. **OSHA defined hazards**Not classified.

Label elements



Signal word Danger

Hazard statement Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious

eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing genetic defects. May cause damage to organs through prolonged or

repeated exposure.

Precautionary statement

PreventionContaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety presquitions have been read and

instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. In case

of inadequate ventilation wear respiratory protection.

5549 Version #: 04 Revision date: 05-07-2025 Issue date: 06-12-2020

Response IF ON SKIN: Wash with plenty of soap and water, IF ON SKIN (or hair): Remove/take off

> immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. Specific treatment (see this label). Take off contaminated clothing and wash before reuse. IF exposed or concerned: Get

Store locked up. Storage

Dispose of contents/container in accordance with local/regional/national/international Disposal

regulations.

medical advice/attention.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
BENZYL ALCOHOL		100-51-6	25 - 35
CYCLOHEXANAMINE, 4,4'-METHYLENEBIS-		1761-71-3	15 - 25
QUARTZ		14808-60-7	10 - 20
1,3-BENZENEDIMETHANAMINE		1477-55-0	5 - 15
[(DIMETHYLAMINO)METHYL]PHEN OL		25338-55-0	1 - 10
3-AMINOPROPYLTRIETHOXYSILAN E		919-30-2	< 1
BENZENE, HYDROXY-		108-95-2	< 1
Other components below reportable	e levels		30 - 40

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a

physician or poison control center immediately.

Skin contact Wash off with soap and water. Take off contaminated clothing and wash before reuse. Wash

clothing separately before reuse. Get medical attention immediately.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Rinse mouth. Do not induce vomiting. If vomiting occurs, the head should be kept low so that Ingestion

> stomach vomit doesn't enter the lungs. Never give anything by mouth to a victim who is unconscious or is having convulsions. Call a POISON CENTER or doctor/physician if you feel

unwell.

Most important symptoms/effects, acute and delayed

May cause allergic skin reaction. Causes serious eye damage. Burning pain and severe corrosive skin damage. Contact may cause redness, burning, drying, and cracking of the skin, and skin damage. Difficulty in breathing.

Indication of immediate medical attention and special treatment needed

Treat symptomatically. Symptoms may be delayed. Keep victim under observation. Keep victim warm.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

and precautions for firefighters

Special protective equipment Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Keep upwind. Keep out of low areas. Ensure adequate ventilation. Ventilate closed spaces before entering them. Wear appropriate personal protective equipment. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get this material in contact with eyes. Do not get this material in contact with skin. Do not get this material on clothing. Provide adequate ventilation. Avoid prolonged exposure. Observe good industrial hygiene practices. Wash thoroughly after handling. Wear appropriate personal protective equipment.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a well-ventilated place.

Store in a closed container away from incompatible materials.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Permissible Expo Components	osure Limits (PEL) for Air Contam Type	inants (29 CFR 19 Value	10.1000) Form
BENZENE, HYDROXY- (CAS 108-95-2)	PEL	19 mg/m3	
		5 ppm	
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 Permissible Expo Components	sure Limits (PEL) for Mineral Dus Type	ts (29 CFR 1910.1 Value	.000) Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Values (TI	.V)		
Components	Туре	Value	Form
1,3-BENZENEDIMETHANAM INE (CAS 1477-55-0)	Ceiling	0.018 ppm	
BENZENE, HYDROXY- (CAS 108-95-2)	TWA	5 ppm	
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
NIOSH. Immediately Dangerous to Li Components	fe or Health (IDLH) Values, as am Type	ended Value	
BENZENE, HYDROXY- (CAS	IDLH	1.8 %	

Material name: NOVOCOAT™ EP3300 PASTE/CAULK PART B

108-95-2)

SDS US

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components

Type

Value

250 ppm

QUARTZ (CAS 14808-60-7) IDLH 50 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)

Components Type Value Form

1,3-BENZENEDIMETHANAM Ceiling 0.1 mg/m3 INE (CAS 1477-55-0)

BENZENE, HYDROXY- (CAS Ceiling 60 mg/m3

108-95-2)

15.6 ppm TWA 19 mg/m3

ΓWA 19 mg/m3 5 ppm

QUARTZ (CAS 14808-60-7) TWA 0.05 mg/m3 Respirable dust.

US. OARS. Workplace Environmental Exposure Level (WEEL) Guide

Components Type Value

BENZYL ALCOHOL (CAS TWA 44.2 mg/m3

100-51-6)

10 ppm

Biological limit values

ACGIH Biological Exposure Indices (BEI)

Components Value Determinant Specimen Sampling Time

BENZENE, HYDROXY- (CAS 250 mg/g Phenol with 108-95-2) Phenol with hydrolysis urine

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

1,3-BENZENEDIMETHANAMINE (CAS 1477-55-0) Can be absorbed through the skin. BENZENE, HYDROXY- (CAS 108-95-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

BENZENE, HYDROXY- (CAS 108-95-2) Skin designation applies.

US - Tennessee OELs: Skin designation

1,3-BENZENEDIMETHANAMINE (CAS 1477-55-0) Can be absorbed through the skin. BENZENE, HYDROXY- (CAS 108-95-2) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

1,3-BENZENEDIMETHANAMINE (CAS 1477-55-0) Danger of cutaneous absorption BENZENE, HYDROXY- (CAS 108-95-2) Danger of cutaneous absorption

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

1,3-BENZENEDIMETHANAMINE (CAS 1477-55-0) Can be absorbed through the skin. BENZENE, HYDROXY- (CAS 108-95-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

BENZENE, HYDROXY- (CAS 108-95-2)

Can be absorbed through the skin.

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet

style gloves.

Other Chemical/oil resistant clothing is recommended.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Material name: NOVOCOAT™ EP3300 PASTE/CAULK PART B

5549 Version #: 04 Revision date: 05-07-2025 Issue date: 06-12-2020

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Paste.

Physical stateLiquid.FormPaste.ColorVarious.

Odor Ammoniacal. Amine-like.

Odor threshold Not available.

pH Alkaline

Melting point/freezing point Not available.

Initial boiling point and boiling range

Not available.

Flash point

Evaporation rate

Flammability (solid, gas)

Not available.

Not available.

Upper/lower flammability or explosive limits

Explosive limit - lower

(%)

Not available.

Not available.

Explosive limit - upper

(%)

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Partial

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 11.72 lb/gal estimated

Specific gravity 1.4 estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stabilityMaterial is stable under normal conditions. **Possibility of hazardous**Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition No hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin contact May cause an allergic skin reaction. Causes severe skin burns and eye damage.

Eye contact Causes serious eye damage.

5549 Version #: 04 Revision date: 05-07-2025 Issue date: 06-12-2020

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Material name: NOVOCOAT™ EP3300 PASTE/CAULK PART B

Symptoms related to the physical, chemical and toxicological characteristics

Causes serious eye damage. May cause an allergic skin reaction. Shortness of breath. Irritating to mouth, throat, and stomach. Contact may cause redness, burning, drying, and cracking of

the skin, and skin damage.

Information on toxicological effects

Acute toxicity

Components Species Test Results

3-AMINOPROPYLTRIETHOXYSILANE (CAS 919-30-2)

<u>Acute</u> Oral

Point estimate* 500 mg/kg bw

BENZYL ALCOHOL (CAS 100-51-6)

<u>Acute</u> Dermal

LD50 Rabbit 2000 mg/kg

Inhalation

LC50 Rat > 4.178 mg/l, 4 Hours

Oral

LD50 Rat 1230 - 3100 mg/kg

CYCLOHEXANAMINE, 4,4'-METHYLENEBIS- (CAS 1761-71-3)

Acute Oral

LD50 Rat 380 mg/kg

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitization May cause sensitization by skin contact. **Germ cell mutagenicity** Suspected of causing genetic defects.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. This

product contains crystalline silica. Silica is a known carcinogen; however in this encapsulated

form the normal routes of exposure are unavailable.

IARC Monographs. Overall Evaluation of Carcinogenicity

BENZENE, HYDROXY- (CAS 108-95-2)

3 Not classifiable as to carcinogenicity to humans.

QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

QUARTZ (CAS 14808-60-7) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity Not available. **Specific target organ toxicity** Not classified.

- single exposure

Specific target organ toxicity

- repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product contains a substance which is toxic to aquatic organisms.

Material name: NOVOCOAT™ EP3300 PASTE/CAULK PART B

5549 Version #: 04 Revision date: 05-07-2025 Issue date: 06-12-2020

^{*} Point estimate = Converted acute toxicity point estimate

Test Results Product Species

NOVOCOAT™ EP3300 PASTE/CAULK PART B

Aquatic

Crustacea EC50 Daphnia 4444.7607 mg/l, 48 hours LC50 Fish Fish 903.2863 mg/l, 96 hours

Components **Test Results Species**

BENZYL ALCOHOL (CAS 100-51-6)

Aquatic Acute

Fish LC50 Bluegill (Lepomis macrochirus) 10 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

BENZENE, HYDROXY-1.46 BENZYL ALCOHOL 1.1

Mobility in soil No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not

discharge into drains, water courses or onto the ground.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the Hazardous waste code

waste disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container

is emptied.

14. Transport information

Not regulated as dangerous goods.

IATA

UN2735 **UN number**

UN proper shipping name Amines, liquid, corrosive, n.o.s. (1,3-BENZENEDIMETHANAMINE)

Transport hazard class(es)

Class 8 **Subsidiary hazard Packing group** TTT **Environmental hazards** Yes **ERG Code** 81

Special precautions for

user

Not assigned.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft Cargo aircraft only

Allowed with restrictions.

IMDG

UN2735 **UN number**

AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. **UN proper shipping name**

(1,3-BENZENEDIMETHANAMINE), MARINE POLLUTANT

Transport hazard class(es)

Class 8 **Subsidiary hazard**

^{*} Estimates for product may be based on additional component data not shown.

Packing group III**Environmental hazards**

Yes Marine pollutant **EmS** F-A, S-B Special precautions for Not assigned.

user

Transport in bulk according to Not available. Annex II of MARPOL 73/78

and the IBC Code

IATA; IMDG



Marine pollutant



15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

BENZENE, HYDROXY- (CAS 108-95-2) 1000 LBS OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

QUARTZ (CAS 14808-60-7)

Cancer lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
BENZENE, HYDROXY-	108-95-2	1000		500	10000
SARA 311/312 Hazardous chemical	Yes				

Material name: NOVOCOAT™ EP3300 PASTE/CAULK PART B 5549 Version #: 04 Revision date: 05-07-2025 Issue date: 06-12-2020 **Classified hazard** categories

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

Germ cell mutagenicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name CAS number % by wt. BENZENE, HYDROXY-108-95-2 < 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

BENZENE, HYDROXY- (CAS 108-95-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

BENZENE, HYDROXY- (CAS 108-95-2) Low priority

US state regulations

California Proposition 65



WARNING: WARNING: This product contains a chemical known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

OUARTZ (CAS 14808-60-7) Listed: October 1, 1988

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 06-12-2020 05-07-2025 **Revision date**

Version # 04

NFPA ratings Health: 3

Flammability: 0 Instability: 0

5549 Version #: 04 Revision date: 05-07-2025 Issue date: 06-12-2020

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Material name: NOVOCOAT™ EP3300 PASTE/CAULK PART B

5549 Version #: 04 Revision date: 05-07-2025 Issue date: 06-12-2020 10 / 10