## SAFETY DATA SHEET



### 1. Identification

Product identifier NOVOCOAT™ EP3300 PASTE/CAULK PART A RESIN, NOVOCOAT™ EP3300 PASTE/CAULK

**SG PART A RESIN** 

Other means of identification None.

**Recommended use**Not available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

**Company Name** ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

**Address** 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

number

1-800-222-7122

Normal work hours

1-877-982-7667

telephone number Website

www.ergonarmor.com sds@ergon.com

**Emergency 24-hour telephone number** 

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

8:00 a.m. to 5:00 p.m.

hours

E-mail

## 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2
Sensitization, skin Category 1
Germ cell mutagenicity Category 2
Carcinogenicity Category 2
Specific target organ toxicity, single exposure Category 1

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, repeated

exposure

Category 1

Specific target organ toxicity, repeated

ed Category 2

exposure

**Environmental hazards** Not classified. **OSHA defined hazards** Not classified.

**Label elements** 



Signal word Danger

**Hazard statement** Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected

of causing genetic defects. Suspected of causing cancer. May cause respiratory irritation. Causes damage to organs through prolonged or repeated exposure. May cause damage to organs

through prolonged or repeated exposure.

**Precautionary statement** 

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or

smoke when using this product. Use only outdoors or in a well-ventilated area.

**Response** IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical

advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. Specific treatment see Section 4 of this SDS. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical

advice/attention.

**Storage** Store in a well-ventilated place. Keep container tightly closed. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

**Supplemental information** None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER	R	28064-14-4	40 - 50
QUARTZ		14808-60-7	5 - 15
M-BIS(2,3-EPOXYPROPOXY)BENZE NE		101-90-6	1 - 10
4,4'-ISOPROPYLIDENEDIPHENOL-E PICHLOROHYDRIN COPOLYMER		25068-38-6	1 - 5
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.		64742-95-6	< 1
Other components below reportable	e levels		37.49

#### 4. First-aid measures

**Inhalation** If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for

breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention, if needed.

**Skin contact** Wash off immediately with soap and plenty of water. Take off contaminated clothing and wash

before reuse. Get medical attention if irritation develops and persists.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention immediately.

Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention.

Most important symptoms/effects, acute and delayed

Skin irritation. May cause an allergic skin reaction. Dermatitis. Rash. Irritant effects. May cause redness and pain. Prolonged exposure may cause chronic effects. May cause respiratory irritation.

Indication of immediate medical attention and special treatment needed

**General information** 

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Keep victim under observation. Contact physician if discomfort continues. Show this safety data sheet to the doctor in attendance.

### 5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dusuitable extinguishing Do not use water je

Water fog. Foam. Dry chemical powder. Alcohol foam. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

media

**Ingestion** 

**Specific hazards arising from** Fire may produce irritating, corrosive and/or toxic gases. **the chemical** 

Special protective equipment and precautions for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Fire fighting equipment/instructions

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. Water runoff can cause environmental damage.

Specific methods

General fire hazards

In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers.

No unusual fire or explosion hazards noted.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Immediately evacuate personnel to safe areas. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not breathe mist or vapor. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Extinguish all flames in the vicinity.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Collect spillage.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Following product recovery, flush area with water.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Do not use in areas without adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Wash hands thoroughly after handling. When using, do not eat, drink or smoke. Avoid release to the environment.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a closed container away from incompatible materials. Keep container tightly closed. Store in a well-ventilated place. Use care in handling/storage. Store in accordance with local/regional/national/international regulation.

### 8. Exposure controls/personal protection

#### Occupational exposure limits

US. OSHA Table Z-1 Permissible E Components	xposure Limits (PEL) for A Type	ir Contaminants (29 CFR 191 Value	.0.1000) Form
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 Permissible E Components	xposure Limits (PEL) for M Type	ineral Dusts (29 CFR 1910.1 Value	000) Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Values Components	s (TLV) Type	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
NIOSH. Immediately Dangerous t Components	o Life or Health (IDLH) Val	ues, as amended Value	

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) **Components Type** Value

**Form** QUARTZ (CAS 14808-60-7) TWA 0.05 mg/m3

**Biological limit values** No biological exposure limits noted for the ingredient(s).

Appropriate engineering Provide adequate ventilation, including appropriate local extraction, to ensure that the defined controls occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Safety glasses. If risk of splashing, wear safety goggles or face shield. **Eye/face protection** 

Skin protection

**Hand protection** Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

Respirable dust.

gloves.

Other Wear appropriate clothing to prevent any possibility of skin contact.

When workers are facing concentrations above the exposure limit they must use appropriate Respiratory protection

certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene Always observe good personal hygiene measures, such as washing after handling the material and considerations before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment

to remove contaminants.

## 9. Physical and chemical properties

**Appearance** Viscous liquid

**Physical state** Liquid. Paste. **Form** Color Various.

Odor Ammoniacal Amine-like.

**Odor threshold** Not available. Not available. pΗ Melting point/freezing point Not available. Initial boiling point and Not available.

boiling range

>392.0 °F (>200.0 °C) Flash point

**Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

**Explosive limit - lower** 

(%)

Not available.

**Explosive limit - upper** 

(%)

Not available.

Vapor pressure Not available. Vapor density Not available. Relative density Not available.

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available. **Viscosity** Not available.

Other information

12.70 lb/gal @25°C **Density** 

1.5 @25°C Specific gravity

## 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport. Chemical stability Material is stable under normal conditions.

Possibility of hazardous

Conditions to avoid

reactions

No dangerous reaction known under conditions of normal use.

Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible

materials.

**Incompatible materials** Peroxides. Chlorine. Strong acids, alkalis and oxidizing agents.

Hazardous decomposition

If product is burned hazardous gases such as oxides of carbon and nitrogen and various hydrocarbons may be produced.

products

## 11. Toxicological information

### Information on likely routes of exposure

**Inhalation** May cause irritation to the respiratory system.

Skin contact Causes skin irritation. **Eve contact** May be irritating to eyes.

**Ingestion** May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics Causes eye irritation. Exposure may cause temporary irritation, redness, or discomfort. May cause

respiratory irritation. Dermatitis. May cause an allergic skin reaction. Rash. Skin irritation.

### Information on toxicological effects

#### **Acute toxicity**

**Product Test Results Species** 

NOVOCOAT™ EP3300 PASTE/CAULK PART A RESIN, NOVOCOAT™ EP3300 PASTE/CAULK SG PART A RESIN

**Acute** 

**Dermal** 

LD50 Rabbit 21667 g/kg

Inhalation

LC50 91000 mg/l, 4 Hours Rat

Oral

LD50 Rat 50 g/kg

Skin corrosion/irritation Serious eye damage/eye

irritation

Causes eye irritation.

Causes mild skin irritation.

Respiratory or skin sensitization

**Respiratory sensitization** Not available.

Skin sensitization May cause sensitization by skin contact. Germ cell mutagenicity Suspected of causing genetic defects.

Carcinogenicity Suspected of causing cancer.

## IARC Monographs. Overall Evaluation of Carcinogenicity

M-BIS(2,3-EPOXYPROPOXY)BENZENE (CAS 101-90-6) 2B Possibly carcinogenic to humans.

OUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. 3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-95-6)

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

QUARTZ (CAS 14808-60-7) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

M-BIS(2,3-EPOXYPROPOXY)BENZENE (CAS 101-90-6) Reasonably Anticipated to be a Human Carcinogen.

QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity

May cause respiratory irritation. Central nervous system.

- single exposure

Specific target organ toxicity May cause damage to organs through prolonged or repeated exposure. Causes damage to organs - repeated exposure through prolonged or repeated exposure. Blood. Stomach. Stomach.

Material name: NOVOCOAT™ EP3300 PASTE/CAULK PART A RESIN. NOVOCOAT™ EP3300 PASTE/CAULK SG PART A RESIN 5548 Version #: 02 Revision date: 06-27-2024 Issue date: 06-27-2024

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

**Aspiration hazard** Not available.

**Chronic effects** Prolonged inhalation may be harmful.

## 12. Ecological information

**Ecotoxicity**The product contains a substance which causes risk of hazardous effects to the environment.

Product Species Test Results

NOVOCOAT™ EP3300 PASTE/CAULK PART A RESIN, NOVOCOAT™ EP3300 PASTE/CAULK SG PART A RESIN

**Aquatic** 

 Crustacea
 EC50
 Daphnia
 11723.3291 mg/l, 48 hours

 Fish
 LC50
 Fish
 11723.3291 mg/l, 96 hours

Acute

Crustacea EC50 Daphnia 12324.5713 mg/l, 48 hours estimated Fish LC50 Fish 12324.3779 mg/l, 96 hours estimated

Components Species Test Results

PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER (CAS 28064-14-4)

Aquatic

Acute

Fish LC50 Fish > 1 - < 10 mg/l

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** Not available.

Partition coefficient n-octanol / water (log Kow)

NOVOCOAT™ EP3300 PASTE/CAULK PART A RESIN, > 3

NOVOCOAT™ EP3300 PASTE/CAULK SG PART A RESIN

**Mobility in soil** No data available.

**Other adverse effects**No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal instructions** Dispose in accordance with all applicable regulations. When this product as supplied is to be

discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code**The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues /

unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Offer rinsed packaging material to local recycling facilities.

### 14. Transport information

DOT

Not regulated as dangerous goods.

**IATA** 

UN number UN3082

**UN proper shipping name** Environmentally hazardous substance, liquid, n.o.s. (PHENOL-FORMALDEHYDE POLYMER

GLYCIDYL ETHER)

Transport hazard class(es)

Class 9
Subsidiary hazard Packing group III
Environmental hazards YES
ERG Code 9L

**Special precautions for** Not assigned.

user

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

aircrait

Cargo aircraft only

Allowed with restrictions.

**IMDG** 

UN number UN3082

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PHENOL-FORMALDEHYDE

POLYMER GLYCIDYL ETHER), MARINE POLLUTANT

Transport hazard class(es)

Class 9

Subsidiary hazard

Packing group

**Environmental hazards** 

Marine pollutant Yes

EmS
Special precautions for

Not assigned.

F-A, S-F

III


user

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

IATA; IMDG



### Marine pollutant



## 15. Regulatory information

**US federal regulations**This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard,

29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

**Toxic Substances Control Act (TSCA)** 

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

**SARA 304 Emergency release notification** 

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

QUARTZ (CAS 14808-60-7) Cancer

lung effects

immune system effects

kidney effects

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

**Classified hazard** Skin corrosion or irritation

categories Serious eye damage or eye irritation

Respiratory or skin sensitization Germ cell mutagenicity

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
M-BIS(2,3-EPOXYPROPOXY)BENZENE	101-90-6	1 - 10

### Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

**Safe Drinking Water Act** Not regulated.

(SDWA)

#### US state regulations

### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

M-BIS(2,3-EPOXYPROPOXY)BENZENE (CAS 101-90-6)

QUARTZ (CAS 14808-60-7)

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. (CAS 64742-95-6)

#### **California Proposition 65**



WARNING: WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

#### California Proposition 65 - CRT: Listed date/Carcinogenic substance

M-BIS(2,3-EPOXYPROPOXY)BENZENE Listed: July 1, 1989

(CAS 101-90-6)

**OUARTZ (CAS 14808-60-7)** Listed: October 1, 1988

### **International Inventories**

Country(s) or region	Inventory name 0	On inventory (yes/no)*		
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes		
Canada	Domestic Substances List (DSL)	Yes		
Canada	Non-Domestic Substances List (NDSL)	No		
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes		
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes		
Europe	European List of Notified Chemical Substances (ELINCS)	No		
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes		
Korea	Existing Chemicals List (ECL)	Yes		
New Zealand	New Zealand Inventory	Yes		
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes		
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes		
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes		
*A IIVaali indicates that all company to af this word of comply with the inventory varying pour a desiriatored by the grounding country (a)				

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

# 16. Other information, including date of preparation or last revision

Issue date 06-27-2024

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**Revision date** 06-27-2024

Version # 02

**NFPA ratings** Health: 2

Flammability: 1 Instability: 0

**References** EPA: AQUIRE database

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any

other materials or in any process, unless specified in the text.

**Revision information** Hazard(s) identification: GHS Signal Words

Physical & Chemical Properties: Multiple Properties Toxicological Information: Toxicological Data

Ecological Information: Ecotoxicity

Transport Information: Proper Shipping Name/Packing Group

Material name: NOVOCOAT™ EP3300 PASTE/CAULK PART A RESIN, NOVOCOAT™ EP3300 PASTE/CAULK SG PART A RESIN 5548 Version #: 02 Revision date: 06-27-2024 Issue date: 06-27-2024