SAFETY DATA SHEET



1. Identification

Product identifier NOVOCOAT™ EP3300 PASTE/CAULK SG PART B HARDENER

Other means of identification None.

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

number

Normal work hours

1-877-982-7667

1-800-222-7122

telephone number

Website www.ergonarmor.com
E-mail sds@ergon.com

Emergency 24-hour telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

hours

8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 1

Serious eye damage/eye irritation

Sensitization, respiratory

Sensitization, skin

Category 1

Sensitization, skin

Category 1

Germ cell mutagenicity

Reproductive toxicity

Specific target organ toxicity, repeated

Category 2

Category 2

exposure

Environmental hazards Not classified. **OSHA defined hazards** Not classified.

Label elements



Signal word Danger

Hazard statement Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious

eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing genetic defects. Suspected of damaging fertility or the unborn child. May cause

damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. IF SWALLOWED:

Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. Specific

treatment see Section 4 of this SDS. Wash contaminated clothing before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
1,3-BENZENEDIMETHANAMINE		1477-55-0	1 - 20
COPOLYMER OF BENZENAMINE AND FORMALDEHYDE, HYDROGENATED		135108-88-2	1 - 20
CYCLOHEXANAMINE, 4,4'-METHYLENEBIS-		1761-71-3	1 - 20
QUARTZ		14808-60-7	1 - 20
AMINE		Proprietary	1 - 10
POLYAMIDOMAINE		Proprietary	1 - 10
PROPRIETARY INGREDIENTS		N/A	1 - 10
[(DIMETHYLAMINO)METHYL]PHEN OL		25338-55-0	1 - < 3
PHENOL		108-95-2	< 0.5
POLYETHYLENEAMINE		Proprietary	< 0.5
Other components below reportabl	e levels		40 - < 50

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Call a physician if symptoms develop or persist.

Skin contact Wash off immediately with soap and plenty of water. Take off immediately all contaminated

clothing. Wash contaminated clothing before reuse. Call a physician or poison control center

immediately.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting

occurs, keep head low so that stomach content doesn't get into the lungs. Never give anything by mouth to a victim who is unconscious or is having convulsions. Call a physician or poison control

center immediately.

Most important symptoms/effects, acute and delayed

ı**nd** Bur Nau

Rash. Birth defects. Long term exposure may affect affect fertility. Causes serious eye damage. Burning pain and severe corrosive skin damage. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. May cause redness and pain. Prolonged exposure may cause

chronic effects.

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical

advice/attention. If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. In the event of fire, cool tanks with water spray. In case of fire and/or explosion do not breathe fumes.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Prevent entry into waterways, sewer, basements or confined areas. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Put material in suitable, covered, labeled containers.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash thoroughly after handling. Avoid release to the environment.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store in a cool, dry place. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)				
Components	Туре	Value	Form	
PHENOL (CAS 108-95-2)	PEL	19 mg/m3		
		5 ppm		
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.	

Material name: NOVOCOAT™ EP3300 PASTE/CAULK SG PART B HARDENER 7788 Version #: 01 Issue date: 07-11-2024

	ΓWA			l mg/m3	Respirable.
			2.	1 mppcf	Respirable.
t Values (TLV)					
• •	Гуре		Va	lue	Form
(Ceiling		0.0	018 ppm	
7	ΓWA		5	opm	
7	ΓWA		0.	025 mg/m3	Respirable fraction.
	-	H) Value	-		
I	[DLH		1.8	3 %	
			25	0 ppm	
		nended	•		Form
					FORIII
(Ceiling		0.	1 mg/m3	
(Ceiling				
				• •	
٦	ΓWA				
				•	
٦	ΓWA		0.0	05 mg/m3	Respirable dust.
alue			Specimen	Sampling 1	Гіme
5. 5	hydrolys		Creatinine in urine	*	
e see the source	document.				
designation					
AMINE (CAS 1477	-				
	on applies				
		Skin de	signation applie	!S.	
AMINE (CAS 1477	•			_	
	_	D	-£	haamatta	
AMIINE (CAS 1477	/-55-U)				
Chemical Haza	ards: Skin des			e la serve	
•	-	Can be	absorbed throu	-	
tor Air Contam	linants (29 Ci		=	ah tha ckin	
		including	appropriate loc	_	o ensure that the define
•	-				
es, such as perso Wear safety gla	-				
	perous to Life of the Chemical Hazarda MINE (CAS 147) Chemical	Type Ceiling TWA TWA TWA Jerous to Life or Health (IDL Type IDLH IDLH To Chemical Hazards Recommand Ceiling Ceiling Ceiling TWA TWA TWA TWA TWA TWA TWA TW	Type Ceiling TWA TWA Jerous to Life or Health (IDLH) Value Type IDLH IDLH Type Ceiling Ceiling Ceiling TWA TWA TWA TWA TWA TWA TWA TW	Type Ceiling Ceiling TWA TWA TWA O.G Ferous to Life or Health (IDLH) Values, as amended Type IDLH IDLH Type Ceiling Ceiling Ceiling Ceiling Ceiling Ceiling Ceiling TWA TWA 19 TWA 19 TWA 19 TWA 19 TWA Ceiling Coiling Ceiling Coiling Ceiling Coiling Ceiling Coiling Ceiling Coiling Coiling	Type Ceiling Ceiling TWA TWA TWA TWA TWA TWA TWA TW

Material name: NOVOCOAT™ EP3300 PASTE/CAULK SG PART B HARDENER

gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Do not get in eyes, on skin, on clothing.

9. Physical and chemical properties

Appearance Viscous liquid

Physical stateLiquid.FormPaste.ColorVarious.

Odor Ammoniacal Amine-like.

Odor thresholdNot available.pHNot available.Melting point/freezing pointNot available.Initial boiling point andNot available.

boiling range

Flash point ≥200.0 °F (≥93.3 °C) Cleveland Open Cup

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.
(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Bulk density 11.7 lb/gal 25°C **Specific gravity** 1.4 @25°C

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. **Possibility of hazardous** Hazardous polymerization does not occur.

Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents. Strong reducing agents. Alkalines. Acids. This product reacts with

hydrofluoric acid. Halogens.

Hazardous decomposition

products

reactions

Carbon dioxide. Carbon monoxide. Nitric Acid. Ammonia. Nitrogen oxide can react with water

vapors to form corrosive nitric acid. Nitrosamine. Aldehydes.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin contact Causes severe skin burns and eye damage. May cause an allergic skin reaction.

Eye contact Causes serious eye damage.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics Exposure may cause temporary irritation, redness, or discomfort. Burning pain and severe corrosive skin damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. May cause respiratory irritation. Symptoms of

overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity

Test Results Components Species

CYCLOHEXANAMINE, 4,4'-METHYLENEBIS- (CAS 1761-71-3)

<u>Acute</u> Oral

LD50 Rat 380 mg/kg

PHENOL (CAS 108-95-2)

Acute Dermal

LD50 Rat 669 mg/kg

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause allergic skin disorders in sensitive individuals.

Germ cell mutagenicity Suspected of causing genetic defects.

This product contains crystalline silica. Silica is a known carcinogen; however in this Carcinogenicity

encapsulated form the normal routes of exposure are unavailable.

IARC Monographs. Overall Evaluation of Carcinogenicity

PHENOL (CAS 108-95-2) 3 Not classifiable as to carcinogenicity to humans.

OUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

QUARTZ (CAS 14808-60-7) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

OUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product Species Test Results

NOVOCOAT™ EP3300 PASTE/CAULK SG PART B HARDENER

Aquatic

Crustacea EC50 Daphnia 4289.7461 mg/l, 48 hours

Material name: NOVOCOAT™ EP3300 PASTE/CAULK SG PART B HARDENER SDS US 6 / 10 7788 Version #: 01 Issue date: 07-11-2024

Product Species Test Results

Fish LC50 Fish 262.6234 mg/l, 96 hours

Acute

Crustacea EC50 Daphnia 880.3037 mg/l, 48 hours estimated Fish LC50 Fish 86.0531 mg/l, 96 hours estimated

Components Species Test Results

PHENOL (CAS 108-95-2)

Aquatic

Acute

Crustacea EC50 Water flea (Daphnia magna) 4.24 - 10.7 mg/l, 48 hours

Fish LC50 Asiatic knifefish (Notopterus notopterus) 6.85 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

PHENOL 1.46

Mobility in soil No data available.

Other adverse effectsNo other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsDispose of this material and its container to hazardous or special waste collection point. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D002: Waste Corrosive material [pH \leq 2 or =>12.5, or corrosive to steel]

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues /

unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

UN number UN2735

UN proper shipping name Amines, liquid, corrosive, n.o.s. (CYCLOHEXANAMINE, 4,4'-METHYLENEBIS-)

Transport hazard class(es)

Class 8
Subsidiary hazard Packing group III
Environmental hazards YES
ERG Code 8L

Special precautions for

user

Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN2735

UN proper shipping name AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.

(CYCLOHEXANAMINE, 4,4'-METHYLENEBIS-), MARINE POLLUTANT

Transport hazard class(es)

Class 8
Subsidiary hazard -

Packing group III

Environmental hazards

Marine pollutant YES EmS F-A, S-B

Special precautions for

use

Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78

Not established.

and the IBC Code



Marine pollutant



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard,

29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)One or more components of the mixture are not on the TSCA 8(b)

inventory or are designated "inactive".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

PHENOL (CAS 108-95-2) Listed.

SARA 304 Emergency release notification

Phenol (CAS 108-95-2) 1000 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

QUARTZ (CAS 14808-60-7) Cancer

lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
PHENOL	108-95-2	1000		500	10000

SARA 311/312 Hazardous Yes

chemical

Material name: NOVOCOAT™ EP3300 PASTE/CAULK SG PART B HARDENER 7788 Version #: 01 Issue date: 07-11-2024

Classified hazard

Skin corrosion or irritation

categories Serious eye damage or eye irritation Respiratory or skin sensitization

Germ cell mutagenicity Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

PHENOL (CAS 108-95-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

PHENOL (CAS 108-95-2) Low priority

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

PHENOL (CAS 108-95-2) QUARTZ (CAS 14808-60-7)

California Proposition 65



WARNING: WARNING: This product contains a chemical known to the State of California to cause cancer. For

more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

OUARTZ (CAS 14808-60-7) Listed: October 1, 1988

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

16. Other information, including date of preparation or last revision

Issue date 07-11-2024

Version # 01 NFPA ratings Health: 3

Flammability: 2 Instability: 0

Material name: NOVOCOAT™ EP3300 PASTE/CAULK SG PART B HARDENER

SDS US 7788 Version #: 01 Issue date: 07-11-2024

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.